




KS-22

3 db VHF fiberglass antenna 1,5 m (5') length

 There's no need to introduce this classic of marine communication. The antenna that has become a standard for users now meets the excellence of the patent 100% WATERPROOF. It's built with a 1,4 mm thick fiberglass whip that gets fully foam injected with the special Scout 100% waterproof technique, and it's ice white colored with high gloss anti-UV filter to prevent color deterioration. The antenna is supplied with 5m RG-58 MIL cable and 1 PL-259 connector to complete the installation on board.

 Non servono presentazioni per questo classico della comunicazione marittima, un antenna che è diventata uno standard per i navigatori incontra l'eccellenza del brevetto 100% WATERPROOF. Costruita con un corpo in vetroresina con spessore di 1,4 mm interamente riempito di poliuretano con la speciale tecnica Scout 100% waterproof, e verniciata con tonalità bianco ghiaccio e filtro anti-UV per prevenire il deterioramento del colore ai raggi solari. Viene fornita con 5m di cavo RG-58 top performance a norme militari e un connettore PL-259 per completare l'installazione a bordo.

 Ein Klassiker, der keiner Erklärung bedarf. Die Antenne, die zum Standard wurde, ist jetzt ausgerüstet mit dem Siegel 100% WATERPROOF. Es hat einen 1,4mm Glasfaser Stab, der mit der speziellen 100% Waterproof Technik komplett schaumgefüllt ist, zusätzlich einen Hochglanz Anti UV-Filter, der die Farbe schützt. Die Antenne wird mit 5 m RG-58 MIL-Kabel und 1 PL-259-Stecker geliefert, um die Installation an Bord abzuschließen.

- ▶ Foam injected - 100% WATERPROOF
- ▶ Anti - UV high gloss finish



Contents / Contenuto / Inhalt

- 1 x Antenna
- 1 x PL-259 (RG-58) male connector twist-on

Technical specifications

Frequency	156-162 MHz
Impedance	50 ohm
Electrical length	1/2 λ
V.S.W.R.	< 1,5:1
Polarization	Vertical
Gain	3 dB
Max power input	50 W
DC Ground	Yes
Whip material	Fiberglass
Ferrule	Reinforced nylon
Coaxial cable	5 m RG-58 CU MIL
Mounting	1" x 14 thread
Length	1,5 m (5')
Weight	0,42 kilo

(code: PF AN NVHF00002)

