

# Multiple Contact Strips



## SPECIFICATION:

|                       |                         |
|-----------------------|-------------------------|
| Contact material      | Gold-Plated Over Nickel |
| Combustibility class  | UL 94 V-0               |
| Connection principle  | Wire-Board              |
| Gender of contacts    | Female                  |
| Temperature range     | -40 ... +85 °C          |
| Pitch                 | 2.54 mm                 |
| Rated current         | 1 A                     |
| Rated voltage         | 250 VAC/VDC             |
| Contact resistance    | 20 mΩ min.              |
| Insulation resistance | 1000 MΩ min.            |
| Withstand voltage     | 500 VAC/min.            |
| Contact brass         | T=0.2 mm                |

| Article Nr.   | Contacts | Dim.A   | Dim.B   |
|---------------|----------|---------|---------|
| RND 205-00817 | 6        | 5 mm    | 12.3 mm |
| RND 205-00818 | 10       | 10.1 mm | 17.4 mm |
| RND 205-00819 | 14       | 15.2 mm | 22.4 mm |
| RND 205-00820 | 16       | 17.7 mm | 25 mm   |
| RND 205-00821 | 20       | 22.8 mm | 30.1 mm |
| RND 205-00822 | 26       | 30.4 mm | 37.7 mm |
| RND 205-00823 | 34       | 40.6 mm | 47.8 mm |
| RND 205-00824 | 40       | 48.2 mm | 55.5 mm |
| RND 205-00825 | 50       | 60.9 mm | 68.2 mm |

