

# UNI-T®



## UT139S

### True RMS Digital Multimeters

UT139S is CAT III 600V digital multimeters designed for electricians. Its NCV feature can effectively check electrical status through measuring EM field intensity. The model includes special features such as LoZ (ACV) for measuring 'ghost' voltage. Its built-in 31-segment analog bar also gives electricians a better visual representation of measurement results. It is built with black EBTN display and it is a perfect meter for working in dark environments.

True  
RMS

True RMS

LoZ

LoZ (ACV)

LPF

LPF



Full range  
protection

EBTN

EBTN display

Technical Specifications		
DC voltage (V)	600V	±(0.5%+2)
AC voltage (V)	600V	±(0.8%+3)
DC current (A)	10A	±(0.7%+2)
AC current (A)	10A	±(1%+3)
Resistance (Ω)	60MΩ	±(0.8%+2)
Capacitance (F)	99.99mF	±(4%+5)
Frequency (Hz)	10Hz~10MHz	±(0.1%+4)
Temperature (°C)	-40°C~1000°C	±(1%+4)
Temperature (°F)	-40°F~1832°F	±(1.5%+5)
Features		
Display count		6000
Auto range/Manual range/True RMS		√
Bandwidth (Hz)		45Hz~400Hz
NCV/Continuity buzzer		√
Duty cycle	0.1%~99.9%	√
Diode		Around 3V
LPF/LoZ (ACV)	CAT III 300V, CAT II 600V	√
Analog bar		√
General Characteristics		
Power	1.5V battery (R6) x 2	
Display	58 x 36mm	
Product color	Red and grey	
Product net weight	345g	
Product size	170 x 80 x 48mm	
Standard accessories	Batteries, test leads, temperature probe	
Standard individual packing	Gift box, English manual	
Standard quantity per carton	20pcs	
Standard carton measurement	450 x 330 x 340mm	
Standard carton gross weight	12.2kg	

